

# CLEVELAND

## VERTICAL CNC BED MILL MODEL: BM-630H

### MACHINE FEATURES:

- Centroid M400 control with 15" LCD
- 15 HP spindle motor, CAT40 spindle taper
- 8,000 rpm spindle speed
- Hardened & ground with Turcite-B coating guide way
- Double nut precision ball screws hardened & ground for high accuracy and long lasting
- FC30 Meehanite casting main frame with annealed & stress relieved for long term reliability
- 100% Laser tested for positioning accuracy & repeatability
- Box ways design on Y & Z axis to provide maximum rigidity & stability
- Standard way covers on all three axes
- Tool box & tools
- Coolant system
- Central lubrication system
- Built-in Quartz work light
- Portable hand wheel (opt)
- AUTOMATIC TOOL CHANGER (opt.)
- FULL ENCLOSURE (opt.)



### Specification

Table: .....	24" x73" (610x1854 mm)
Longitudinal travel: .....	59" (1500 mm)
Cross travel: .....	33.5" (850 mm)
Vertical travel: .....	28" (710 mm)
Spindle nose to table top (D): .....	4.7" to 28.3" (120-720 mm)
Load capacity: .....	3300 lbs (1500 kgs)
Spindle taper: .....	BT40 or CAT40
Spindle speed: .....	60 to 8000 rpm
Transmission of spindle & motor: .....	Belts
Spindle center to column front surface: .....	25.5" (650 mm)
T slot: .....	0.7*5*2.7" mm

### Feed Rate

Rapid feed rate: .....	X/Y/Z: 250 ipm AC
Cutting feed rate: .....	1 to 120 ipm

### Motor

Spindle motor/max torque: .....	15 HP
Feed motors on XYZ: .....	2 kW - AC Servo
Coolant pump: .....	1/8 Hp
Lubrication pump:.....	150 W
Power requirement: .....	20 KVA, 3 Phase 208V to 230V (Max)

### Automatic Tool Changer

No. of tools: .....	OPT
Max tool diameter: .....	3.5" (90 mm)
Max tool weight: .....	15 lbs (7 kgs)

### Dimension & Weight

Length x Width x Height: .....	175" x 105" x 115"
Net weight: .....	11000 lbs (5000 kgs)

## Standard Accessories

Tools & box	Leveling bolts & plate	RS-232 interface
Operation manual	15" color LCD	Splash guard
Auto lube system	Halogen work light	120 GB solid state hard drive
USB 2.0 port	Coolant system	Shop floor programming/Conversational

## Optional Machine Accessories

CK-105	52pcs Clamping Kit
CP-MIST	Mist Coolant System
16ATC	16 T magazine - Umbrella with Software
ENCLOSURE	Full Enclosure
SEMI-ENCLOU	Semi Enclosure
CHIP	Chip Auger
C40RK-45	Retention Knob Cat40, 45degree 20pcs
TG-CNC	Table Guard
TRAN-17KVA	Transformer: 28KVA (440~480V)
Riser Block	10" riser block for Engine block job shop
WISE-6	6" Angle Vise W/ Swivel Base (Import)

## Optional Software Accessories

10620	Compression tapping
10610	User definable Macros and sub programs [M98 & G65]
10851	Cutter compensation
10360	4th axis software
10630	Unlimited part program size
10730	Intercon off-line conversational program (for your desktop PC)
10810	Rigid tapping [G74 & G 84] (includes 10620)
10850	Coordinate system rotation (CSR)
10625	Scaling and mirroring [G50 & G51]
10814	DXF in, CAD drawing input software
10660	BCD tool change output
10740	Engraving software

### Digitizing & Probing

10405	DP-4 probing package w/ CSR (10850)
12486	DP-7 probing package w/ CSR (10850)
10770	2D & 3D digitizing software (requires 10405)
10220	TT-1; Tool touch off kit
12468	TT-2; Tool touch off kit
10772	Tool room package (10405 & 10220 & 10600 work coordinate)

### Manual Pulse Generators (MPG)

11069	100 Step MPG
-------	--------------

## Additional Accessories Information

Power requirement: ..... 20 KVA 3 phase 208V to 230V (Max)  
Air requirement: ..... With opt. power draw bar 90 - 100 psi  
Type of oil for way oil / oil chiller / pneumatic oil: .... Mobil Vectra #2/ Shell Tellus 32/ Air tool oil  
Coolant capacity: ..... 16 Gallons

**\*\* WE RESERVE THE RIGHT TO CHANGE DESIGN, COLOR, SPECIFICATIONS, OR PRICE WITHOUT NOTICE \*\***

# CLEVELAND MACHINERY SALES INC.

5000 BROOKPARK ROAD  
CLEVELAND, OHIO 44134

PHONE: 216-741-8900  
FAX: 216-741-8995

WEBSITE: [www.clevelandmachinery.com](http://www.clevelandmachinery.com) EMAIL: [sales@clevelandmachinery.com](mailto:sales@clevelandmachinery.com)