

CLEVELAND

HEAVY DUTY 30~32 SERIES CNC LATHE WITH CENTROID T400 CONTROL



MACHINE FEATURES:

- Rugged Meehanite Casting,
- Hardened and Ground Bed ways,
- Turcit-B lined on sliding ways & Gibbs with precision hand scraped
- Std. 4" spindle hole DELTA Vector Spindle drives with maxi Torque at auto gear shifting in 3-gear range
- Precision ground ball-screw w/double nuts
- Dual electric hand-wheels for manual operation
- manual Tailstock
- The M/C's with Automatic Lubrication
- Halogen Work light, Coolant system
- Telescopic steel way cover on X-Axis
- Full Enclosed guarding
- Made in Taiwan

CNC LATHE SPECIFICATIONS:

MODEL	SPINDLE	SWING OVER BED	CENTER DISTANCE	SPINDLE SPEED	SPINDLE MOTOR	AXES MOTOR
KL-3060	4"/A2-11	30.3"(770 mm)	59.05"(1500 mm)	20 -1500 rpm	15 HP	2KW/1KW
KL-3080	4"/A2-11	30.3"(770 mm)	78.74"(2000 mm)	20 -1500 rpm	15 HP	2KW/1KW
KL-30120	4"/A2-11	30.3"(770 mm)	118.11"(3000 mm)	20 -1500 rpm	15 HP	2KW/1KW
KL-30160	4"/A2-11	30.3"(770 mm)	157.48"(4000 mm)	20 -1500 rpm	15 HP	2KW/1KW
KL-3260	4"/A2-11	33.0"(840 mm)	59.05"(1500 mm)	20 -1500 rpm	15 HP	2KW/1KW
KL-3280	4"/A2-11	33.0"(840 mm)	78.74"(2000 mm)	20 -1500 rpm	15 HP	2KW/1KW
KL-32120	4"/A2-11	33.0"(840 mm)	118.11"(3000 mm)	20 -1500 rpm	15 HP	2KW/1KW
KL-32160	4"/A2-11	33.0"(840 mm)	157.48"(4000 mm)	20 -1500 rpm	15 HP	2KW/1KW
KL-32200	4"/A2-11	33.0"(840 mm)	196.85"(5000mm)	20-1200 rpm	15 Hp	3KW/1KW

CONTROL FEATURES:

HARDWARE:

- 15" COLOR VGA LCD SCREEN
- X & Z DEDICATED JOG BUTTONS
- USER FRIENDLY CONTROLS
- COOLANT FUNCTIONS
- SPINDLE & BRAKE FUNCTIONS
- PC BASED
- PC STYLE SEALED FULL FEATURE KEYBOARD
- DIGITAL AC SERVO DRIVES AND MOTORS
- 1GB SOLID STATE HARD DRIVE
- USB 2
- RS-232, MOUSE & PARALLEL PORTS

SOFTWARE:

- PC BASED TECHNOLOGY, SOFTWARE UPDATEABLE & HIGH SPEED BLOCK THROUGHPUT
- CONVENTIONAL PROGRAMMING
- TOOL PATH GRAPHICS, TURNING CYCLES, GROOVING CYCLES, DRILLING CYCLES, TAPPING CYCLES, CUTOFF CYCLE, THREADING CYCLES, STOCK REMOVAL CYCLES, POSITION LINE AND ARC EVENTS, INTEGRATED TOOL LIBRARY, RUN TIME ESTIMATES GRAPHICAL MATH HELP & AUTOMATIC CORNER RADIUS.
- G-CODES & FULL M-FUNCTION CONTROL
- TOOL FUNCTIONS, TOOL COMPENSATION
- PART PROGRAM STORAGE AND EDITING • PROGRAM STORAGE, FULL SCREEN UNLIMITED FILE SIZE TEXT EDITOR, READ/WRITE TO FLOPPY DISK, SAVE PROGRAMS VIA COM PORTS.
- AXIS CONTROL • CONSTANT SURFACE SPEED CONTROL, HIGH SPEED CONTOURING, BACKLASH COMPENSATION, PITCH ERROR COMPENSATION, LEAST INPUT INCREMENT OF .0001", 2000 LINE LOOK AHEAD ACCEL/DECEL, QUADRATURE ENCODER INTERFACE.
- FEED FUNCTION • RAPID TRAVERSE, RAPID TRAVERSE OVERRIDE JOG PANEL KEY SELECTABLE, RAPID TRAVERSE AUTOMATIC ACCEL/DECEL, FEEDRATE OVERRIDE 2 TO 200% VARIABLE.
- UTILITIES • FORMAT FLOPPY COMMAND, BACKUP DATA & SYST. FILES, RESTORE DATA & SYST. FILES IMPORT/EXPORT, DRAG PLOT, PLC AND SYSTEM DIAGNOSTICS & MOTOR TEMPERATURE ESTIMATING.

**** WE RESERVE THE RIGHT TO CHANGE DESIGN, COLOR, SPECIFICATIONS, OR PRICE WITHOUT NOTICE ****

CLEVELAND MACHINERY SALES INC.

**5000 BROOKPARK ROAD
CLEVELAND, OHIO 44134
WEBSITE: www.clevelandmachinery.com**

**PHONE: 216-741-8900
FAX: 216-741-8995
EMAIL: sales@clevelandmachinery.com**