CLEVELAND

VERTICAL MACHINING CENTER MODEL: M1600 / M1600L

MACHINE FEATURES:

- Centroid M400 control with 15" LCD
- 24 tools ATC arm type
- 25 HP spindle motor, BT50 or CAT50 spindle taper
- 4,500 rpm spindle speed with spindle oil cooler
- Hardened & ground with Turcite-B coating guide way
- Double nut precision ball screws hardened & ground for high accuracy and long lasting
- FC30 Meehanite casting main frame with annealed & stress relieved for long term reliability
- 100% laser tested for positioning accuracy & repeatability
- 4 Box ways design on Y axis to provide maximum rigidity & stability
- Telescopic steel way covers on all three axes
- Tool box & tools
- Coolant system and air blast system
- Central lubrication system
- Built-in Quartz work light
- Rigid tapping (opt)
- Portable hand wheel (opt)

| CLEVELAND | | | | |
|-------------|-----|-----|---------|---|
| M1600/1600L | | | 00000 | 7 |
| 77 | | | Rations | h |
| | 200 | | | - |
| | | 119 | | U |
| | | 13 | | |
| | | | | |

| Specification | |
|--|---|
| X / Y / Z travel: | 63" / 31.5" / 31.5" (M1600) 63" / 39.3" / 31.5" (M1600L) |
| Distance from spindle to column: | 33.8" (M1600) 41.7" (M1600L) |
| Distance from spindle to table top: Working Table | 6.7" ~ 38.1" |
| Size (X / Y): | 70.8" / 31.5" |
| T-slot: | |
| Load capacity: ····· | 5500 lbs |
| Spindle | |
| Motor: | 25 HP |
| Speed: ····· | |
| Taper: ····· | CAT50 / BT50 |
| Feed Rate | |
| Rapid X / Y / Z: ····· | 420 / 420 / 360 ipm |
| Cutting: | 240 ipm |
| ATC | |
| Tool magazine capacity: | |
| Max. tool dia. / adj. pocket empty: | Ø 4.1" / Ø 8.6" |
| Max. tool length: | |
| Max. tool weight: | 33 IDS |
| General | 40.16)/4 |
| Power requirement:Pneumatic tank requirement (min.): | |
| Coolant tank capacity: | |
| Dimension & Weight | 77 yai |
| L X W X H: | 181" v 126" v 123" |
| Weight: ······ | 30,800 lbs |
| vvoigiit. | 00,000 103 |

Standard Accessories

Booster (unclamp) cylinder

Full enclosure

Coolant system

Telescoping way cover

Tools & box

Air gun & spindle air blast

Halogen work light

Operation manual

Encoder set

Screw type chip auger Electric cabinet set w/ bracket Arm type 24 tool atc system

Optional Machine Accessories

CK-105 52pcs Clamping Kit slot: 0.71" (18mm); stud: 5/8-11

CP-MIST Mist Coolant System

UG-MT15 Upgrade to high torque Y and Delta Motor VISE-6 6" Angle Vise W/ Swivel Base (Import) C40RK-45 Retention Knob Cat40, 45degree 20pcs

100 Step MPG

CP-SP Coolant Through Spindle

Optional Software Accessories

11069

| 10620 | Compression tapping | |
|-------------------------------|--|--|
| 10610 | User definable Macros and sub programs [M98 & G65] | |
| 10851 | Cutter compensation | |
| 10360 | 4th axis software | |
| 10630 | Unlimited part program size | |
| 10730 | Intercon off-line conversational program (for your desktop PC) | |
| 10810 | Rigid tapping [G74 & G 84] (includes 10620) | |
| 10850 | Coordinate system rotation (CSR) | |
| 10625 | Scaling and mirroring [G50 & G51] | |
| 10814 | DXF in, CAD drawing input software | |
| 10660 | BCD tool change output | |
| 10740 | Engraving software | |
| Digitizing & Probing | | |
| 10405 | DP-4 probing package w/ CSR (10850) | |
| 12486 | DP-7 probing package w/ CSR (10850) | |
| 10770 | 2D & 3D digitizing software (requires 10405) | |
| 10220 | TT-1; Tool touch off kit | |
| 12468 | TT-2; Tool touch off kit | |
| 10772 | Tool room package (10405 & 10220 & 10600 work coordinate) | |
| Manual Pulse Generators (MPG) | | |

^{**} WE RESERVE THE RIGHT TO CHANGE DESIGN, COLOR, SPECIFICATIONS, OR PRICE WITHOUT NOTICE **

CLEVELAND MACHINERY SALES INC.

5000 BROOKPARK ROAD PHONE: 216-741-8900 CLEVELAND, OHIO 44134 FAX: 216-741-8995

WEBSITE: www.clevelandmachinery.com EMAIL: sales@clevelandmachinery.com