

CLEVELAND

VERTICAL CNC BED MILL MODEL: BM600H

MACHINE FEATURES:

- **Centroid M400 control with 15" LCD**
- **15 HP spindle motor, CAT40 spindle taper**
- **8,000 rpm spindle speed**
- Hardened & ground with Turcite-B coating guide way
- Double nut precision ball screws hardened & ground for high accuracy and long lasting
- FC30 Meehanite casting main frame with annealed & stress relieved for long term reliability
- 100% Laser tested for positioning accuracy & repeatability
- Box ways design on Y & Z axis to provide maximum rigidity & stability
- Standard way covers on all three axes
- Tool box & tools
- Coolant system
- Central lubrication system
- Built-in Quartz work light
- **Portable hand wheel (opt)**
- **AUTOMATIC TOOL CHANGER (opt.)**
- **FULL ENCLOSURE (opt.)**



Specification

Table:	17.7" x 70.8" (450x1800 mm)
Longitudinal travel:	59" (1500 mm)
Cross travel:	24.4" (620 mm)
Vertical travel:	23.6" (600 mm)
Spindle nose to table top (D):	4.7" to 28.3" (120-720 mm)
Load capacity:	2200 lbs (1000 kgs)
Spindle taper:	BT40 or CAT40
Spindle speed:	60 to 8000 rpm
Transmission of spindle & motor:	Belts
Spindle center to column front surface:	25.5" (650 mm)
T slot:	0.62*3*2.36" mm

Feed Rate

Rapid feed rate:	X/Y/Z: 250 ipm
AC Cutting feed rate:	1 to 120 ipm

Motor

Spindle motor/max torque:	15 HP / 10 kW
Feed motors on XYZ:	2 kW - AC Servo
Coolant pump:	1/8 Hp
Lubrication pump:	150 W
Power requirement:	20 KVA, 3 Phase 208V to 230V (Max)

Automatic Tool Changer

No. of tools:	OPT
Max tool diameter:	3.5" (90 mm)
Max tool weight:	15 lbs (7 kgs)

Dimension & Weight

Length x Width x Height:	175" x 102.7" x 110.5"
Net weight:	9460 lbs (4300 kgs)

Standard Accessories

Tools & box	Leveling bolts & plate	RS-232 interface
Operation manual	15" color LCD	Splash guard
Auto lube system	Halogen work light	120 GB solid state hard drive
USB 2.0 port	Coolant system	Shop floor programming/Conversational

Optional Machine Accessories

CK-105	52pcs Clamping Kit
CP-MIST	Mist Coolant System
16ATC	16 T magazine - Umbrella with Software
ENCLOSURE	Full Enclosure
SEMI-ENCLOU	Semi Enclosure
CHIP	Chip Auger
C40RK-45	Retention Knob Cat40, 45degree 20pcs
TG-CNC	Table Guard
TRAN-17KVA	Transformer: 28KVA (440~480V)
Riser Block	10" riser block for Engine block job shop
WISE-6	6" Angle Vise W/ Swivel Base (Import)

Optional Software Accessories

10620	Compression tapping
10610	User definable Macros and sub programs [M98 & G65]
10851	Cutter compensation
10360	4th axis software
10630	Unlimited part program size
10730	Intercon off-line conversational program (for your desktop PC)
10810	Rigid tapping [G74 & G 84] (includes 10620)
10850	Coordinate system rotation (CSR)
10625	Scaling and mirroring [G50 & G51]
10814	DXF in, CAD drawing input software
10660	BCD tool change output
10740	Engraving software

Digitizing & Probing

10405	DP-4 probing package w/ CSR (10850)
12486	DP-7 probing package w/ CSR (10850)
10770	2D & 3D digitizing software (requires 10405)
10220	TT-1; Tool touch off kit
12468	TT-2; Tool touch off kit
10772	Tool room package (10405 & 10220 & 10600 work coordinate)

Manual Pulse Generators (MPG)

11069	100 Step MPG
-------	--------------

Additional Accessories Information

Power requirement: 20 KVA 3 phase 208V to 230V (Max)

Air requirement: With opt. power draw bar 90 - 100 psi

Type of oil for way oil / oil chiller / pneumatic oil: Mobil Vectra #2/ Shell Tellus 32/ Air tool oil

Coolant capacity: 16 Gallons

**** WE RESERVE THE RIGHT TO CHANGE DESIGN, COLOR, SPECIFICATIONS, OR PRICE WITHOUT NOTICE ****

CLEVELAND MACHINERY SALES INC.

**5000 BROOKPARK ROAD
CLEVELAND, OHIO 44134**

**PHONE: 216-741-8900
FAX: 216-741-8995**

WEBSITE: www.clevelandmachinery.com EMAIL: sales@clevelandmachinery.com