

CLEVELAND

OFFICE TYPE VMC MODEL: S8 SPACE SAVER SMART MILL

MACHINE FEATURES:

- Centroid M400i control with 15" LCD
- 8 tools ATC armless
- 1.5 HP spindle motor, BT30 spindle taper
- 8,000 rpm spindle speed
- 3 axes linear guide way
- Precision ball screws for high accuracy and long lasting
- FC30 Meehanite casting main frame with annealed & stress relieved for long term reliability
- 100% laser tested for positioning accuracy & repeatability
- Telescopic steel way covers on all three axes
- Tool box & tools
- Coolant system and air blast system
- Central lubrication system
- Rigid tapping (opt)
- Portable hand wheel (opt)



Specification

Table:	32" x 9.45"
Longitudinal travel:	15.37"
Cross travel:	9.45"
Vertical travel:	13.75"
Spindle nose to table top (D):	1.18" to 14.95"
Load capacity:	220 lbs
Spindle taper & pull force:	BT 30 & 300 kgs
Spindle speed:	8000 rpm
Transmission of spindle & motor:	Belts
Spindle center to column front surface:	10"

Feed Rate

Rapid feed rate:	X/Y: 300ipm Z: 300 ipm
rate:	1 to 100 ipm

Motor

Spindle motor/max torque:	1.55 HP
Feed motors on XYZ:	0.75 kW
Coolant pump:	1/8 Hp
Lubrication pump:	150 W
Power requirement:	10 KVA, 3 Phase 208V to 230V (Max)

Automatic Tool Changer

No. of tools:	8
Max tool diameter:	2" (50 mm)
Max tool weight:	10 lbs (4 kgs)

Dimension & Weight

Length x Width x Height:	74" x 48" x 79"
Net weight:	2,640 lbs (1200 kgs)

Standard Accessories

Tools & box	Leveling bolts & plate	RS-232 interface
Operation manual	Full enclosure	Air blast, coolant flush gun
Auto lube system	Halogen work light	60 GB solid state hard drive
USB 2.0 port	Coolant system	Shop floor programming/Conversational

Optional Machine Accessories

Oil Skimmer	Oil Skimmer
Air Gun	Air Gun
BT30-45	Retention Knob BT30, 45 degree (10 pcs)
CK-105	52pcs Clamping Kit
CP-MIST	Mist Coolant System
TRAN-17	Transformer: 17KVA (440~480V)
UG-MT	Upgrade Motor to 3HP

Optional Software Accessories

10620	Compression tapping
10610	User definable Macros and sub programs [M98 & G65]
10851	Cutter compensation
10360	4th axis software
10630	Unlimited part program size
10730	Intercon off-line conversational program (for your desktop PC)
10810	Rigid tapping [G74 & G 84] (includes 10620)
10850	Coordinate system rotation (CSR)
10625	Scaling and mirroring [G50 & G51]
10814	DXF in, CAD drawing input software
10660	BCD tool change output
10740	Engraving software

Digitizing & Probing

10405	DP-4 probing package w/ CSR (10850)
12486	DP-7 probing package w/ CSR (10850)
10770	2D & 3D digitizing software (requires 10405)
10220	TT-1; Tool touch off kit
12468	TT-2; Tool touch off kit
10772	Tool room package (10405 & 10220 & 10600 work coordinate)

Manual Pulse Generators (MPG)

11069	100 Step MPG
-------	--------------

Additional Accessories Information

Power requirement: 10 KVA 3 phase 208V to 230V (Max)
Air requirement: 90 - 100 psi
Type of oil for way oil / pneumatic oil: Mobil Vectra #2/ Shell Tellus 32/ Air tool oil
Coolant capacity: 10 Gallons
.

****WE RESERVE THE RIGHT TO CHANGE DESIGN, COLOR, SPECIFICATIONS, OR PRICE WITHOUT NOTICE****

CLEVELAND MACHINERY SALES INC.

5000 BROOKPARK ROAD
CLEVELAND, OHIO 44134

PHONE: 216-741-8900
FAX: 216-741-8995

WEBSITE: www.clevelandmachinery.com EMAIL: sales@clevelandmachinery.com